DESOI PullDevice H-1

No. 11570

Description

mobile, pneumatic pulling device DESOI PullDevice H-1 with a double-acting cylinder and switching to automatic mode for pulling the ram injection lances.

Delivery range

with electric hydraulic unit 230 V, moving device, a double-acting special cylinder with through bore Ø 30 mm, holding plate for drawing head, $2 \times 5 \text{ m}$ hydraulic hose Ø 6 mm and remote control, incl. instruction manual

Advantages

- Usable for ram injection lances G $\frac{1}{4}^{\prime\prime}$ or G $\frac{1}{2}^{\prime\prime}$
- Mobility by moving device
- Tightening speed adjustable
- Easy operation



2. Automatic switching

| Technical data | |
|-------------------------------|----------------------|
| Power supply | 230 V/50Hz |
| Motor power | approx. 1.1 kW |
| Working pressure | max. 100 bar |
| Pull-out force | max. approx. 2400 kg |
| Pull-out path (piston stroke) | max. 100 mm |
| Tank capacity | 2.81 |
| Type of oil | HLP 46 |
| Weight | 56 kg |
| LxWxH | 60 x 55 x 81 cm |
| | |

| Accessories | No. |
|-----------------------------|-------|
| Pulling head ¼" hydraulic | 11560 |
| Pulling head 1/2" hydraulic | 11565 |

All information and data in this technical data sheet are based on the current state of technology. We reserve the right to make technical modifications. The consumption data given here are average values based on experience therefore deviations cannot be excluded. 08/2018

